



Our Mission: Your Protection.

ROCK SAFETY Kft. | 5100 Jászberény, Nagykátai út 10.

HUN

TÁJÉKOZTATÓ

a TAIPAN cikkszámú védőkesztyű rendeltetészerű használatához

Importőr: ROCK SAFETY Kft. Cím: 5100 Jászberény, Nagykátai út 10.

A védőeszköz megnevezése: Ötujjas védőkesztyű mikroorganizmusok (baktériumok és gombák) és vegyszerek ellen

Cikkszám: TAIPAN

EU-típusvizsgálati tanúsítvány száma: 2777/24073-01/E28-01

A megfelelőségértékelést végző bejelentett szervezet:

SATRA Technology Europe Ltd. (Azonosító szám: 2777)

Bracetown Business Park. Clonee. D15YN2P. Írország

EU-megfelelőségi nyilatkozat – Azonosító: TAIPAN-4

– Elérhető: rocksafety.com

VÉDELMI KÉPESSÉG

A védőkesztyű védelmet biztosít mikroorganizmusok (baktériumok és gombák) okozta kockázatok és vegyszerekkel való érintkezés vagy vízzel való tartós érintkezés esetén.

VÉDELMI FOKOZAT

A védőkesztyű megfelel az Európai Parlament és a Tanács (EU) 2016/425 Rendeletében meghatározott követelményeknek.

EN 420:2003+A1:2009, EN ISO 21420:2020 és

EN ISO 21420:2020/A1:2024 – A kéz mozgási képessége: 5.

EN ISO 374-5:2016 – Védelem baktériumok és gombák ellen.

EN ISO 374-1:2016+A1:2018/B típus	Védelmi fokozat	EN ISO 374-4:2019 Degradáció
n-Heptán (J)	2	50,6%
40%-os Nátrium-hidroxid (K)	6	-7,1%
96%-os Kénsav (L)	1	100,0%
25%-os Ammónium-hidroxid (O)	6	27,0%
30%-os Hidrogén-peroxid (P)	4	27,1%
37%-os Formaldehid (T)	5	17,7%

JELKÉPEK

Minden 50 db-os gyűjtőcsomagoláson feltüntetett jelképek az alábbiak:

Mikroorganizmusokkal szembeni védelem jele + információ jele:

Vegyszerekkel szembeni védelem jele:



Élelmiszeripari felhasználhatóság jele:



CE-jelölés:



Ugyanitt kerül feltüntetésre a gyártó logója, a védőkesztyű cikkszáma, a kesztyű mérete, a gyártás ideje, a védőkesztyű elhasználódási ideje.

A védőkesztyű elérhető méretei: S, M; L; XL; 2XL (7; 8; 9; 10; 11)

ALAPANYAG ÉS FORMAI KIALAKÍTÁS

Narancs színű, gyémánt textúrált nitrilkaucsuk. Vastagság: ≥ 0,16 mm. Súly (M méret): ≥ 6,5 g. Mártott kesztyű. Mindkét kézen használható.

TISZTÍTÁS, KARBANTARTÁS

A védőkesztyű egyszer használatos, nem tisztítható, nem fertőtleníthető.

TÁROLÁS

Szellős, száraz, hűvös helyen, fénytől védve; eredeti csomagolásban.

CSOMAGOLÁS

Papír dobozban 50 darabos kiszerelésben, tájékoztatóval ellátva.

Gyűjtőcsomagolás: 500 darabos papírkarton dobozban, azonosításra alkalmas jelöléssel ellátva.

HASZNÁLAT

- A védőkesztyű ismert allergiát okozó anyagot, szereket nem tartalmaz.
- Csak tiszta, száraz kézre húzzunk fel védőkesztyűt.
- Csak teljesen ép, sértetlen, száraz védőkesztyű biztosít megfelelő védelmet és vehető használatba.
- A védőkesztyű elhasználódási ideje: a gyártástól számított 10 év.
- Vegyük figyelembe, hogy a munkavégzés körülményei eltérhetnek a munkavédelmi megfelelőséget megállapító vizsgálatától.
- A TAIPAN védőkesztyű csomagolásán feltüntetett információ: a gyártó neve és címe; a védőkesztyű cikkszáma és mérete; a gyártás ideje, az elhasználódási idő; a tájékoztató elérhetősége; a mikroorganizmusokkal szembeni védelem a megfelelő jelképpel és a vonatkozó szabványszámmal; CE-jelölés.
- A tájékoztató nem tükrözi a védelem – munkahelyen tapasztalható – tényleges időtartamát, illetve a keverékek/elegyek és a tisztá vegyszerek hatása közötti különbségeket.
- A vegyszerekkel szembeni ellenállás laboratóriumi körülmények között, csak a tenyérreőrésből vett minták vizsgálatával került meghatározásra (kivéve a 400 mm-nél hosszabb védőkesztyűket, ahol a mandzsettát is vizsgálni kell), és csak a vizsgálathoz használt vegyszer(ek)re vonatkozik. A védőkesztyű által biztosított ellenállás eltérő lehet, ha az adott vegyszer keverékben/elegyben található.
- Javasolt annak ellenőrzése, hogy a védőkesztyű valóban megfelel a tervezett felhasználásra, mert a munkahelyi körülmények eltérhetnek a típusvizsgálati körülményektől, pl. a fellépő hőmérséklet, koptató és degradációs hatások tekintetében.
- A használt védőkesztyű, megváltozott fizikai tulajdonságai miatt, alacsonyabb ellenállást tanúsíthat a veszélyes vegyszerekkel szemben. A tényleges használhatósági időt jelentősen lecsökkentheti a mozgás, beakadás, dörzsölés, a vegyszer okozta degradáció stb. Korrozív vegyszerek esetében a degradációs ellenállás lehet a legfontosabb tényező a vegyi kockázatok elleni védőkesztyű kiválasztásakor.
- A vegyszerbehatolással szembeni ellenállás laboratóriumi körülmények között került meghatározásra, és csak a vizsgált mintára vonatkozik.
- A védőkesztyű vírusokkal szemben nem került vizsgálatra!
- A védőkesztyű teljesíti a „Bfr XXI. Ajánlás (2016.07.01.) III. Kategória” alapkövetelményeit, amely szerint élelmiszerekkel érintkezhet.
- Az egyéni védőeszköz használata és kezelése feleljen meg a 65/1999. (XII. 22.) EüM rendelet előírásainak.



Our Mission: Your Protection.

ROCK SAFETY Kft. | 5100 Jászberény, Nagykátai Street 10, Hungary

ENG BROCHURE

on the proper use of protecting gloves with Art. No.: TAIPAN

Importer: ROCK SAFETY Kft.

Address: 5100 Jászberény, Nagykátai Street 10, Hungary

Type of the personal protective equipment: Five-finger protective gloves against microorganisms (bacteria and fungi) and chemicals

Article number: TAIPAN

No. of the EU type-examination certificate: 2777/24073-01/E28-01

Notified body involved in the conformity:

SATRA Technology Europe Ltd. (NB: 2777)

Bracetown Business Park. Clonee. D15YN2P. Republic of Ireland.

EU declaration of conformity – ID: TAIPAN-4

– Available: rocksafety.com

The protective glove provides protection against hazards caused by microorganisms (bacteria and fungi) and contact with chemicals or prolonged contact with water.

PROTECTION LEVEL

The protective glove complies with the requirements set forth in Regulation (EU) 2016/425 of the European Parliament and of the Council.

EN 420:2003+A1:2009, EN ISO 21420:2020 and

EN ISO 21420:2020/A1:2024 – Dexterity: 5.

EN ISO 374-5:2016 – Protection against bacteria and fungi.

EN ISO 374-1:2016+A1:2018/Type B	Protection level	EN ISO 374-4:2019 Degradation
n-Heptane (J)	2	50.6%
40% Sodium hydroxide (K)	6	-7.1%
96% Sulphuric acid (L)	1	100.0%
25% Ammonium hydroxide (O)	6	27.0%
30% Hydrogen peroxide (P)	4	27.1%
37% Formaldehyde (T)	5	17.7%

SYMBOLS

All symbols shown on every 50-piece collector box are as follows:

Marking of protection against microorganisms + information:



Marking of usability in food industry:



Marking of protection against chemicals



CE marking:



The manufacturer's logo, the article number of the protective gloves, the size of the gloves, the date of manufacture, and the service life of the protective gloves will all be indicated here.

Available sizes of the protective gloves: S, M; L; XL; 2XL (7; 8; 9; 10; 11)

MATERIAL AND DESIGN

Orange, diamond textured nitrile rubber. Thickness: ≥ 0.16 mm.

Weight (size M): ≥ 6.5 g. Dipped gloves. Ambidextrous.

CLEANING, MAINTENANCE

The protective gloves are single-use, non-cleanable, and non-decontaminable.

STORAGE

In a spacious, dry, cool place, protected from light, in the original packaging.

PACKAGING

Packaged in a paper box of 50 pieces, accompanied by an information leaflet.

Collective packaging: in a paperboard box of 500 pieces, marked with an identification label.

USE

- The protective gloves do not contain any known allergenic substances or chemicals.
- Only wear protective gloves on clean, dry hands.
- Only intact, undamaged, and dry protective gloves provide adequate protection and can be put to use.
- The shelf life of the protective gloves is 10 years from the date of manufacture.
- Please consider that the working conditions may differ from those established in the workplace safety conformity assessment.
- Information indicated on the TAIPAN protective gloves packaging includes: the manufacturer's name and address; the article number and size of the gloves; the date of manufacture, shelf life; contact information for inquiries; protection against microorganisms indicated with the appropriate symbol and corresponding standard number; CE marking.
- The resistance to chemicals has been determined under laboratory conditions, based solely on samples taken from the palm area (except for gloves longer than 400 mm, where the cuff must also be examined), and is applicable only to the specific chemical(s) used in the testing. The resistance provided by the gloves may differ if the specific chemical is present in a mixture or formulation.
- It is recommended to verify that the gloves are indeed suitable for the intended use, as workplace conditions may vary from those of the type testing, for example, regarding the effects of temperature, abrasion, and degradation.
- Due to the altered physical properties of used protective gloves, they may exhibit lower resistance against hazardous chemicals. The actual usability time can be significantly reduced by factors such as movement, snagging, abrasion, and degradation caused by chemicals, among others. In the case of corrosive chemicals, the resistance to degradation may be the most critical factor when selecting protective gloves against chemical hazards.
- The resistance to chemical penetration was determined under laboratory conditions and applies only to the tested sample.
- The protective gloves have not been tested against viruses!
- The protective gloves meet the basic requirements of „BfR Recommendation XXI (2016.07.01.) Category III,” which states that they may come into contact with food.