



Our Mission: Your Protection.

ROCK SAFETY Kft. | 5100 Jászberény, Nagykúti út 10.

HUN

TÁJÉKOZTATÓ

a ROADRUNNER(W) cikkszámu védőkesztyű
rendeltetésszerű használatáhozInformációs
piktogram:

CE-jelölés:



Ugyanitt kerül feltüntetésre a gyártó logója, a védőkesztyű cikk-száma, a kesztyű mérete, a gyártás ideje, a védőkesztyű elhaszná-lódási ideje.

A védőkesztyű elérhető méretei: S; M; L; XL; 2XL, 3XL

ALAPANYAG ÉS FORMAI KIALAKÍTÁS

Alapanyag:

Marha színbőr kesztyű.
Textil meleg bélés membránnal.

TISZTÍTÁS, KARBANTARTÁS

A kesztyű nem mosható.

TÁROLÁS

Szellős, száraz, hűvös helyen, fénytől védve; eredeti csomago-lásban.

CSOMAGOLÁS

Nylon tasakban 10 páras kiszerezésben, tájékoztatóval ellátva.
Gyűjtőcsomagolás: 50 pár papírkarton dobozban, azonosításra alkalmas jelöléssel ellátva.

HASZNÁLAT

- A védőkesztyű ismert allergiát okozó anyagot, szereket nem tartalmaz.
- Csak tiszta, száraz kézre húzzunk fel védőkesztyűt.
- Csak teljesen ép, sértetlen, száraz védőkesztyű biztosít megfe-lelő védelmet és vehető használatba.
- A védőkesztyű elhasználódási ideje: a gyártástól számított 10 év.
- Vegyük figyelembe, hogy a munkavégzés körülményei eltér-hetnek a munkavédelmi megfelelőséget megállapító vizsgá-latétól.
- A ROADRUNNER(W) védőkesztyű csomagolásán feltüntetett információ: a gyártó neve és címe; a védőkesztyű cikkszáma és mérete; a gyártás ideje, az elhasználódási idő; a tájékoztató el-érhetősége; mechanikai (3222X) és hideg elleni (321) védelmi szintek a megfelelő jelképpel és a vonatkozó szabványszám-mal; CE-jelölés; figyelmeztetés, hogy a feltüntetett védelem csak a kesztyű tenyér részén érvényes.
- A védőkesztyű nem használható abban az esetben, ha felme-rül a mozgó alkatrészekbe/berendezésekbe való beakadás kockázata.
- A védőkesztyű használata során megengedett maximális ex-pozíció (pl. hőmérséklet, idő) meghatározását a használat körülményeinek és a védőkesztyű védelmi képességének is-meretében az MSZ EN ISO 11079:2008 szabvány szerint lehet elvégezni.
- A védőkesztyű nedvesség hatására elveszítheti hideggel szem-ben szigetelő tulajdonságát.
- Az egyéni védőeszköz használata és kezelése feleljen meg a 65/1999. (XII. 22.) EüM rendelet előírásainak.

Gyártó: ROCK SAFETY Kft.

Cím: 5100 Jászberény, Nagykúti út 10.

A védőeszköz megnevezése: Ötujjas védőkesztyű mechani-kai kockázatok és hideg ellen

Cikkszám: ROADRUNNER(W)

EU-típusvizsgálati tanúsítvány száma: EU-0475-K/2020

A megfelelőségértékelést végző bejelentett szervezet:

BIMEO Vizsgáló és Kutató-fejlesztő Kft. (NB 1524)

1047 Budapest, Attila u. 64.

EU-megfelelőségi nyilatkozat – Azonosító: ROADRUNNER(W)-4

– Elérhetőség: www.rocksafty.com

VÉDELMI KÉPESSÉG

A védőkesztyű védelmi fokozatának megfelelő védelmet biztosít anyagok által okozott koptató, vágó, szakító és szűrő mechanikai hatások, valamint sugárzó és kontakt hideg hatásával szemben. A feltüntetett védelem csak a kesztyű tenyér részére érvényes!

VÉDELMI FOKOZAT

A védőkesztyű megfelel az Európai Parlament és a Tanács (EU) 2016/425 Rendeletében meghatározott követelményeknek.

MSZ EN 420:2003+A1:2010 A kéz mozgási képessége: 3

MSZ EN 388:2017

Mechanikai védelmi szint: 3 2 2 2 X, részletezve:

Tulajdonság	Védelmi szint	Mért érték
kopásállóság	3	2800 c
késvágással szembeni ellenállás (Coupe)	2	2,5
továbbszakító erő	2	26 N
átlukasztással szembeni ellenállás	2	64 N
vágással szembeni ellenállás (TDM)	X	–


MSZ EN 511:2006

Hideg elleni védelmi szint: 3 2 1, részletezve:

Tulajdonság	Védelmi szint	Mért érték
sugárzó hideg	3	0,23 m²K/W
kontakt hideg	2	0,079 m²K/W
vízállóság	1	> 5 min

JELKÉPEK

Minden páron, mandzsettába varrott címkén vagy kézhátra nyomtatva feltüntetett jelképek az alábbiak:

Mechanikai
vizsgálati jel:Hideg elleni
vizsgálati jel:



Our Mission: Your Protection.

ROCK SAFETY Kft. | 5100 Jászberény, Nagykátai Street 10., Hungary

ENG

BROCHURE

on the proper use of protective gloves
model No. ROADRUNNER(W)

Name of the manufacturer: ROCK SAFETY Kft.

Address: Nagykátai út 10., H-5100 Jászberény, Hungary

Type of the personal protective equipment: Five fingered
protective gloves against mechanical risks and cold
Model No.: ROADRUNNER(W)

No. of the EU type-examination certificate: EU-0475-K/2020

Notified body involved in the conformity:

BIMEO Vizsgáló és Kutató-fejlesztő Kft. (NB 1524)

Attila u. 64., H-1047 Budapest, Hungary

EU declaration of conformity – ID: ROADRUNNER(W)-4

– Available: www.rocksafty.com

The protective gloves provide protection against abrasive, cutting, tearing and piercing mechanical risks, as well as against the effects of convective and contact cold, according to their protection level. The indicated protection only pertains to the palm of the gloves!

PROTECTION LEVEL

The protective gloves meet the requirements specified in Regulation (EU) 2016/425 of the European Parliament and of the Council.

EN 420:2003+A1:2009

Dexterity: 3

EN 388:2016

Mechanical protection level: 3 2 2 2 X, in details:



Property	Protection level	Measured value
Abrasion resistance	3	2800 c
Blade cut resistance (Coupe)	2	2.5
Tear resistance	2	26 N
Puncture resistance	2	64 N
Cut resistance (TDM)	X	–

EN 511:2006 Cold protection level: 3 2 1, in details:

Property	Protection level	Measured value
Convective cold	3	0.23 m²K/W
Contact cold	2	0.079 m²K/W
Water penetration	1	> 5 min

MARKINGS

The following markings are present on each protective glove:

Mechanical
tests marking:Cold tests
marking:Information
pictogram:

CE-marking:



The logo of the manufacturer, as well as the model number, the size, the date of manufacture and the period of obsolescence of the protective gloves are also marked on the gloves.

Available sizes of the protective gloves: S; M; L; XL; 2XL, 3XL

COMPONENT MATERIALS AND DESIGN

Component materials:

- Gloves made from full grain bovine leather.
- Warm textile lining with membrane.

CLEANING, MAINTENANCE

The gloves are not washable.

STORAGE

Under airy, dry, cool and dark conditions; in the original packaging.

PACKAGING

10 pairs in a nylon bag with a brochure.

50 pairs per carton with identification markings.

USE

- The protective gloves do not contain any materials or compounds that are known to cause allergic reactions.
- Only use the gloves on clean and dry hands.
- Only an intact and dry glove will provide adequate protection. If a defective protective glove is found it should be damaged noticeably and not used.
- The period of obsolescence of the protective gloves is: 10 years after manufacture.
- Take into account that the conditions at the workplace may differ from the conditions of the conformity testing.
- The following information is marked on the packaging of the ROADRUNNER(W) protective gloves: the name and address of the manufacturer; the model number and size of the protective gloves; the date of manufacture and the period of obsolescence; where the manufacturer's instructions and information is available; the mechanical protection level (3222X) and the cold protection level (321) with the appropriate pictograms and the relevant standard numbers; the CE marking; a warning that the indicated protection only pertains to the palm of the gloves.
- The gloves must not be worn if there is a risk of entanglement by moving parts of machines.
- The maximum permissible user exposure (e.g. temperature, time) can be determined according to the EN ISO 11079:2007 standard, based on the conditions of use and the protection level of the gloves.
- The protective gloves may lose their insulative properties when wet.